

GO WITH THE FLOW.



Mobile AdBlue® dispensing equipment

# BlueMobil 60: Dispensing AdBlue® Mobile and user-friendly

**NEW!**

The **BlueMobil 60** is a brand new designed, electrically operated solution for mobile AdBlue®-dispensing in workshops used for cars and vans. The compact construction and integrated battery pack makes the **BlueMobil 60** an independent and flexible tool for daily use in workshops.

Also the automatic dispensing nozzle and the unique FMT 3 flow meter, specially developed by TECALEMIT, offer extreme ease of use and user satisfaction.

#### Advantages:

- battery operated with integrated 12 V battery charger for flexible use
- integrated FMT 3 flow meter for optimal measurement of the volume of AdBlue® dispensed
- selectable flow rates  
High-Flow of approx. 8 l/min.  
Low-Flow of approx. 4.5 l/min.
- LED battery level indicator
- protective housing with integrated nozzle holder
- with 4 swivel casters for easy manoeuvrability within even the tightest of spaces

[www.tecalemit.de](http://www.tecalemit.de)



MADE IN  
**GERMANY**  
Durable Quality

A HORNGROUP COMPANY

GO WITH THE FLOW.

### BlueMobil 60:

Prod. no. see below

The **BlueMobil 60** is the electrically operated solution for mobile AdBlue®-Dispensing in workshops for cars and vans.

The **BlueMobil 60** tap system is to be used exclusively with AdBlue® urea solution. The reservoir tank contains ca. 60 liters and can be easily replaced with containers up to 60 l from standard manufacturers.

### Scope of delivery:

- solid carriage with four swivel casters
- electric membrane pump
- FMT 3 flow meter
- 2 m dispensing hose with kink protection
- automatic AdBlue®-nozzle
- 60 l storage tank
- battery with charging indicator
- charger and cable

### Technical characteristics

Voltage:	12 V
Nominal current:	15 A
Capacity:	0.15 kW
Power-on time:	100 %
Protection class:	IP 54
Pump type:	membrane pump
Conveying capacity:	app. 8 l/min. app. 4.5 l/min.
Max. conveying pressure:	5.0 bar
Valve pressure limit:	min. 5.5 bar
Battery charger range:	100 V-240 V, 50/60 Hz, 60 W
Battery:	12 V VRLA, 36 Ah
Charging time:	app. 6 h
Battery life after charging:	app. 25 dispenses of each 10 l
Dispensing hose:	DN 19
Filters:	630 µm
Pressure port:	3/4"
Suction nozzle:	3/4"
Medium temperature:	- 7°C to + 30°C
Ambient temperature:	- 10°C to + 50°C
Dimensions (W × D × H):	460 × 730 × 1.330 mm
Weight:	approx. 70 kg

015599260

BlueMobil 60



TECALEMIT is your partner for the professional delivery, filling and measurement of fuel, oil, grease, air and chemicals.

**HORN GmbH & Co.**  
**Limited partnership**  
Munketoft 42  
24937 Flensburg  
Germany

T +49 461 8696-0  
F +49 461 8696-66  
info@tecalemmit.de  
[www.tecalemmit.de](http://www.tecalemmit.de)

