

Mobile AdBlue® dispensing equipment

BlueMobil eco:

Dispensing AdBlue® simple and quick



The pneumatically operated AdBlue®-dispenser **BlueMobil eco** is the simple and cost-effective solution for mobile AdBlue®-dispensing in workshops used for cars and vans.

Also the automatic dispensing nozzle and the unique FMT 3 flow meter, specially developed by TECALEMIT, offer extreme ease of use and user satisfaction.

Advantages:

- integrated FMT 3 flow meter for optimal measurement of the volume of AdBlue[®] dispensed
- selectable flow rates
 High-Flow of approx. 8 I/min.
 Low-Flow of approx. 4.5 I/min.
- Integrated nozzle holder
- with 4 swivel casters for easy manoeuvrability within even the tightest of spaces
- 2 tank sizes (60 l or 120 l)
- simple to use wihtin the compressed air network in workshops

www.tecalemit.de





BlueMobil eco

Art.-no. see below

The **BlueMobil eco** is the pneumatically operated solution for mobile AdBlue®-Dispensing in workshops for cars and vans. The cost-effective but solid construction is ideal for the use in small workshops. The installed tap system should be used exclusively with AdBlue® urea solution. The **BlueMobil eco** is available in **two** sizes: **60I** or **120I**.

Scope of delivery:

- solid carriage with four swivel casters
- pneumatic membrane pump
- FMT 3 flow meter
- 2m dispensing hose
- automatic AdBlue®-nozzle
- 60 | or 120 | storage tank
- plug & use in your compressed air network

Technical characteristics

Pump type: membrane pump Flow rate: app. 8 l/min. app. 4.5 l/min.

Max. conveying pressure: 6.0 bar Compressed air inlet: min. 6 bar, max. 10 bar

Dispensing hose: DN 19 Air pressure center spigot: DN 7.2 630 µm Pressure port: 3/4" Suction nozzle: 3/4"

- 7°C to + 30°C Medium temperature: Ambient temperature: - 10°C to + 50°C 483 × 680 × 1096 mm Dimensions (W \times D \times H):

Weight: app. 38 kg

015599060	BlueMobil 60 eco
015599120	BlueMobil 120 eco







TECALEMIT is your partner for the professional delivery, filling and measurement of fuel, oil, grease, air and chemicals.

HORN GmbH & Co. KG Munketoft 42 24937 Flensburg Germany

T+49 461 8696-0 F +49 461 8696-66 info@tecalemit.de www.tecalemit.de

