



HORNET W 50 II FMT II

# **HORNET W 50 II HORNET W 50 II Z 300 HORNET W 50 II FMT II**

**Electric operating drum and container pump HORNET W 50 II  
for diesel, heating oil EL/L (minimum flash point  $\geq 55^{\circ}\text{C}$ )  
and radiator anti-freeze (undiluted).**

**Choose for your application the appropriate electric pump  
from HORN TECALEMIT**

Electric pumps for diesel, heating oil EL/L and radiator anti-freeze (undiluted), self-priming with integrated anti-siphon protection, drum thread R 2", incl. suction hose with filter for 1600 mm immersion depth and 4,0 m discharge hose, DN 19 x 4, with A 2010 approved design automatic nozzle and swivel hose joint.

The new principle of construction permits a fast and safe self-priming.

**HORNET W 50 II** 230 V~  
Article no. 106 508 700

**HORNET G 50/12 II** 12 V  
Article no. 106 538 700

**HORNET G 50/24 II** 24 V  
Article no. 106 548 700



- Capacity approx. 55 l/min\* (230 V~)
- (Standard version)
- Automatic nozzle A 2010 with swivel hose joint

**HORNET W 50 II Z 300** 230 V~  
Article no. 106 618 700

**HORNET G 50/12 II Z 300** 12 V  
Article no. 106 638 700

**HORNET G 50/24 II Z 300** 24 V  
Article no. 106 648 700



- Capacity approx. 50 l/min\* (230 V~)
- (Standard version)
- Automatic nozzle A 2010 with swivel hose joint
- Mechanical roller counter Z 300, not calibratable

**HORNET W 50 II FMT II** 230 V~  
Article no. 106 518 701

**HORNET G 50/12 II FMT II** 12 V  
Article no. 106 558 701

**HORNET G 50/24 II FMT II** 24 V  
Article no. 106 568 701



- Capacity approx. 52 l/min\* (230 V~)
- (Standard version)
- Automatic nozzle A 2010 with swivel hose joint
- Flow meter FMT II

\*Depending on viscosity and system

**HORN GmbH & Co. KG**  
Munketoft 42  
24937 Flensburg  
Germany

T +49 461 8696-11/20  
F +49 461 8696-98  
info@tecalem.it  
www.tecalemit.de