



HORNET W 40 A FMT II

HORNET W 40 HORNET W 40 FMT II

**Electrically operating drum and container pump
for fuel and diesel (minimum flash point $\geq 55^{\circ}\text{C}$)**

**There is a HORN TECALEMIT electric pump suitable
for all your application needs**

Electro pumps for diesel and fuel oil, priming level with integrated anti-siphon safety feature, ON / OFF-key and indicator lamp, motor with thermo switch protection, drum thread M 64 x 4 and G 2", suction hose included with filter for a suction head of 1600 mm, 4 m of nozzle hose DN 19 x 4 Horn 40X, anti-kink spring and standard nozzle or automatic nozzle A 2010.

Installing hand pump below the electric pump enables a fast and safe pumping as well as an emergency operation in case of a power loss. Furthermore, a controlled dispensing of small rates is possible.

HORNET W 40 230 V~
Item no. 104 428 700

HORNET G 40/12 12 V
Item no. 104 438 700

HORNET G 40/24 24 V
Item no. 104 448 700



- Capacity approx. 40 l/min* (230 V~)
- (standard version)
- Standard nozzle ZP 19 with hose swivel joint

HORNET W 40 FMT II 230 V~
Item no. 104 458 701

HORNET G 40/12 FMT II 12 V
Item no. 104 468 701

HORNET G 40/24 FMT II 24 V
Item no. 104 478 701



- Capacity approx. 35 l/min* (230 V~)
- (standard version)
- Standard nozzle ZP 19 with hose swivel joint
- flow meter FMT II

HORNET W 40 A 230 V~
Item no. 104 528 700

HORNET G 40/12 A 12 V
Item no. 104 538 700

HORNET G 40/24 A 24 V
Item no. 104 548 700



- Capacity approx. 35 l/min* (230 V~)
- (standard version)
- Automatic nozzle A 2010 with hose swivel joint

HORNET W 40 A FMT II 230 V~
Item no. 104 558 701

HORNET G 40/12 A FMT II 12 V
Item no. 104 568 701

HORNET G 40/24 A FMT II 24 V
Item no. 104 578 701



- Capacity approx. 35 l/min* (230 V~)
- (standard version)
- flow meter FMT II
- Automatic nozzle A 2010 with hose swivel

FMT II
Item no. 253 590 000
for assembly on
HORNET W 40



*Depending on viscosity and system

**Pneumatic Components Ltd.
(PCL)**

Holbrook Rise
Holbrook Industrial Estate
Sheffield S20 3GE
United Kingdom

T +44 114 248 2712
F +44 114 247 8342
info@pclairtechnology.com
www.pclairtechnology.com